

Christie GS Series

Boardrooms
Conference rooms
Education spaces
Government
Live event staging
Museums
Themed parks and attractions
Worship facilities



Long-life 1DLP laser projectors

CHRISTIE[®]



◀ 630-GS and 635-GS available only in white except for China, where it is only available in black.

Long-life laser projectors with a low cost of ownership

Avoid downtime, cost of lamp replacements and maintenance by choosing the Christie® GS Series of solid state illumination projectors for your next project. From business venues to events and beyond, professional-grade Christie GS Series models deliver great performance and reliability in high-usage environments.

Featuring laser phosphor illumination, the Christie GS Series typically provides 20,000 hours of low-cost operation. Wireless connectivity, a small footprint, lightweight, quiet operation and a full suite of lenses makes the GS Series ideal for boardrooms, conference rooms, education, worship facilities, live event staging and other small and medium venues.

Including proprietary Christie BoldColor Technology in our 850-GS and 1075-GS models, takes 1DLP® laser phosphor to even higher levels of brightness and image quality with even more accurate color reproduction.



▶ 850-GS is available in black or white. The 1075-GS is available in black only.



Christie GS Series

All Christie® GS Series projectors deliver accurate color reproduction, image quality and high-brightness. Christie 850-GS and 1075-GS models include proprietary Christie BoldColor Technology for the most life-like images and natural color reproduction possible with laser phosphor illumination – an industry first.

| | | Christie DHD630-GS | Christie DWU630-GS | |
|------------------------|--|--|---|--|
| Image | brightness | <ul style="list-style-type: none"> • 6125 ISO lumens (typical) • 5400 Center lumens (typical) • 5400 ANSI lumens (typical) | <ul style="list-style-type: none"> • 6750 ISO lumens (typical) • 6000 Center lumens (typical) • 6000 ANSI lumens (typical) | |
| | color wheel | • 4 Segment (RGBY) - 2X or 3X speed | | |
| | contrast (full on/full off) | <ul style="list-style-type: none"> • Full On/Off (Christie RealBlack™ enabled): 4,000,000:1 • Dynamic contrast 6000:1 • Full On/Off (Christie RealBlack disabled): 1200:1, ANSI 250:1 | | |
| Display technology | type | • 1-chip 0.65" DMD S600HB | • 1-chip 0.67" DMD S600HB | |
| | native resolution | • 1920 x 1080 (2,073,600 pixels) (16:9) | • 1920 x 1200 (2,304,000 pixels) (16:10) | |
| | color control | • Features precise software color adjustments for hue, saturation and gain. Adjust the hue of each primary color component (red, green, blue and white) for perfecting images on an individual projector or for matching colors across multiple adjacent displays | | |
| Illumination | type | • High Efficiency Blue Laser Phosphor | | |
| | performance | • 20,000 hrs to 50% brightness | | |
| Inputs | standard | <ul style="list-style-type: none"> • HDMI x 2 • DVI-D x 1 (digital only) • HD15 x 1 • Remote in: 3.5mm stereo female (provides serial communications and power) • HDBaseT (RJ45 x 1) • RJ45 x 1 (Control over wired network connection) | | |
| | 3D | <ul style="list-style-type: none"> • HDMI 1.4, HDBaseT – frame packed, top/bottom, side-by-side/frame sequential • Up to 120Hz output • Does not support Frame Sequential 3D • 3D Sync out (BNC) – for genlocking projectors or controlling emitter or polarizer | | |
| | signals | <ul style="list-style-type: none"> • HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio (all inputs) | | |
| | pixel clock | • 162 MHz | | |
| | scan rates | • Horizontal: 15-91kHz • Vertical: 24-120Hz | | |
| | Signal outputs | monitor out | • HD15 x 1 | |
| | Warping and blending | • None | | |
| Control and networking | <ul style="list-style-type: none"> • RS232 In • Control via HDBaseT • Ethernet (10/100) RJ45 • Built-in backlit keypad • IR remote • Wired remote control (3.5mm stereo) | | | |
| Lens mount | type | • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment | | |
| Lenses | offsets | <ul style="list-style-type: none"> • ±100% Vertical (540 pixels) • ±30% Horizontal (288 pixels) | <ul style="list-style-type: none"> • ±100% Vertical (±600 pixels) • ±30% Horizontal (±288 pixels) | |
| | optional | <ul style="list-style-type: none"> • Lens 0.75-0.95 Zoom G/GS (140-119102-01) • Lens 0.95-1.22 Zoom G/GS (140-101103-01) • Lens Zoom Std G/599-GS 1.22-1.53 (G/555/599/630-GS/635-GS) (140-132107-01) • Lens Zoom HP G/GS 1.22-1.52 (All G & GS) (140-131106-01) • Lens 1.52-2.89 Zoom G/GS (140-102104-01) • Lens 2.9-5.50:1 Zoom G/GS (140-107109-01) • Lens UST 0.36 (120") Ultra short throw lens, 630/635/700/850/1075-GS (140-133108-01) | | |
| Accessories | standard | • IR Remote with wired remote jack (wire not included) • AC line cord for projector head • User manual | | |
| | optional | <ul style="list-style-type: none"> • Christie One Mount (108-506102-01) • One Mount Extender Rod (121-125109-01) • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod) (121-126100-01) • Cable Cover GS White (140-106108-01) | | |
| Power requirements | operating voltage | • Normal: 100-240 VAC @ 50/60 Hz | | |
| | power consumption | • Normal mode: 650W | | |
| | operating current | • Normal mode: 9.5A (100V-240V) | | |
| | dissipation | • 97.5W | | |
| Audible noise | • Standard mode: 36dB(A) • Eco mode: 34dB(A) | | | |
| Physical | size | • (LxWxH): 19.9 x 17.95 x 7.6" (505 x 456 x 190mm) w/o feet or lens | | |
| | shipping size | • (LxWxH): 24.65 x 23.43 x 13.74" (626 x 596 x 349mm) | | |
| | weight | • 34.94lbs (15.85kg) w/o lens | | |
| | shipping weight | • 47.06lbs (21.35kg) | | |
| Environment | operating conditions | • 32-104°F (0-40°C) • Humidity: 10-85% non-condensing | | |
| Regulatory | <ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • CE • FDA • CCC • KC • PSE • EAC • SABS • BIS • VCCI • RCM • Ukr • TER • SASO | | | |
| Warranty | <ul style="list-style-type: none"> • Three years on the projector • Three years or 15,000 hours on the illumination system¹ • Contact an authorized Christie representative for full details of our limited warranty | | | |

¹ Reference the Christie Standard Limited Warranty document for details.



| Christie DHD635-GS | Christie DWU635-GS | Christie DHD850-GS | Christie DWU850-GS |
|---|---|--|---|
| <ul style="list-style-type: none"> • 6125 ISO lumens (typical) • 5400 Center lumens (typical) • 5400 ANSI lumens (typical) | <ul style="list-style-type: none"> • 6750 ISO lumens (typical) • 6000 Center lumens (typical) • 6000 ANSI lumens (typical) | <ul style="list-style-type: none"> • 7750 ISO lumens (typical) • 7200 Center lumens (typical) • 6900 ANSI lumens (typical) | <ul style="list-style-type: none"> • 8400 ISO lumens (typical) • 8000 Center lumens (typical) • 7500 ANSI lumens (typical) |
| | | <ul style="list-style-type: none"> • Full On/Off (Christie RealBlack enabled): 300,000:1 • Dynamic Contrast: 6000:1 • Full On/Off (Christie RealBlack disabled): 1200:1, ANSI: 250:1 | |
| <ul style="list-style-type: none"> • 1-chip 0.65" DMD S600HB | <ul style="list-style-type: none"> • 1-chip 0.67" DMD S600HB | <ul style="list-style-type: none"> • 1-chip 0.65" DMD | <ul style="list-style-type: none"> • 1-chip 0.67" DMD |
| <ul style="list-style-type: none"> • 1920 x 1080 (2,073,600 pixels) (16:9) | <ul style="list-style-type: none"> • 1920 x 1200 (2,304,000 pixels) (16:10) | <ul style="list-style-type: none"> • 1920 x 1080 (2,073,600 pixels) (16:9) | <ul style="list-style-type: none"> • 1920 x 1200 (2,304,000 pixels) (16:10) |
| <ul style="list-style-type: none"> • Solid state (laser phosphor) with Christie BoldColor Technology | | | |
| | | <ul style="list-style-type: none"> • HDMI x 2 (one on rear panel, one of bottom of projector, independently selectable) • 3GSDI x 1 (BNC) • DVI-D x 1 (Digital only) • VGA x 1 • USB x 1 (type B mini) - display over USB • USB x 1 (type A) - image viewer or Wi-Fi® dongle (optional) • HDBaseT (RJ-45 x 1) • RJ-45 x 1 (ChristiePresenter over wired network connection) | |
| <ul style="list-style-type: none"> • HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side/frame sequential • Up to 120Hz output • 3D Sync in (BNC) - for genlocking projectors • 3D Sync out (BNC) - for genlocking projectors or controlling emitter or polarizer | <ul style="list-style-type: none"> • HDMI 1.4, HDBaseT - frame packed, top/bottom, side by side, up to 120Hz output • 3D Sync in (BNC) - for genlocking projectors • 3D Sync out (BNC) - for genlocking projectors or controlling emitter or polarizer | | |
| | | <ul style="list-style-type: none"> • Horizontal: 15-91kHz • Vertical: 24-85Hz | |
| <ul style="list-style-type: none"> • Embedded warping and blending (no option board required) | | <ul style="list-style-type: none"> • 3GSDI x 1 (BNC) | |
| | | <ul style="list-style-type: none"> • RS-232 in • Control via HDBaseT • Ethernet (10/100) RJ-45 with ChristieNET™ connectivity • Built-in backlit keypad • Wired remote control (3.5mm stereo) - Loop out available for daisy chaining | |
| <ul style="list-style-type: none"> • ±100% Vertical (540 pixels) • ±30% Horizontal (288 pixels) | <ul style="list-style-type: none"> • ±100% Vertical (±600 pixels) • ±30% Horizontal (±288 pixels) | <ul style="list-style-type: none"> • ±120% Vertical (±648 pixels) • ±30% Horizontal (±288 pixels) | <ul style="list-style-type: none"> • ±100% Vertical (±600 pixels) • ±30% Horizontal (±288 pixels) |
| <ul style="list-style-type: none"> • 0.75-0.95: Lens 0.75-0.95 Zoom G (140-119102-XX) • 0.95-1.22: Lens 0.95-1.22 Zoom G (140-101103-XX) • 1.22-1.52: Lens Zoom HP G/GS 1.22-1.52 (140-131106-XX) • 1.52-2.89: Lens 1.52-2.89 Zoom G (140-102104-XX) • 2.90-5.50: Lens 2.9-5.50:1 Zoom G (140-107109-XX) • Mechanical lens-shift range: ±50% (WUXGA) or ±60% (HD) Vertical, ±15% Horizontal | | | |
| <ul style="list-style-type: none"> • QwikRig Rigging Frame (140-128102-02) • Christie One Mount Plus (140-117100-XX) • One Mount Extender Rod (121-125109-01) • Wireless dongle (133-113106-01) • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod) (121-126100-01) | | | |
| <ul style="list-style-type: none"> • Normal mode: 820W ±15% (220V), 850W ±15% (110V) • Normal mode: 3.9A ±15% (220V), 7.8A ±15% (110V) • Normal mode: 2796 BTU/hr (220V), 2900 BTU/hr (110V) | | | |
| <ul style="list-style-type: none"> • Standard mode: 35dB(A) • Eco Mode: 32dB(A) | | | |
| <ul style="list-style-type: none"> • (LxWxH): 22.2 x 19.2 x 7.6" (555 x 480 x 190mm) w/o feet • (LxWxH): 30.4 x 24.1 x 14.9" (759 x 599 x 373mm) | | | |
| <ul style="list-style-type: none"> • 52.4lbs (23.7kg) • 66.3lbs (30kg) | | | |





| Christie DHD1075-GS | Christie DWU1075-GS |
|---|---|
| <ul style="list-style-type: none"> • 10,000 ISO lumens (typical) • 9000 Center lumens (typical) • 8800 ANSI lumens (typical) | <ul style="list-style-type: none"> • 10,875 ISO lumens (typical) • 9500 Center lumens (typical) • 9500 ANSI lumens (typical) |
| <ul style="list-style-type: none"> • Full On/Off (Christie RealBlack enabled): 2,000,000:1 • Dynamic contrast: 6000:1 • Full On/Off (Christie RealBlack disabled): 1200:1 • ANSI 250:1 | |
| <ul style="list-style-type: none"> • 1-chip 0.65" DMD • 1920 x 1080 (2,073,600 pixels) (16:9) | <ul style="list-style-type: none"> • 1-chip 0.67" DMD • 1920 x 1200 (2,304,000 pixels) (16:10) |
| <ul style="list-style-type: none"> • HDMI x 1 • 3GSDI x 1 (BNC) | |
| <ul style="list-style-type: none"> • RS232 In • Control via HDBaseT • Ethernet (10/100) RJ45 • Built-in backlit keypad • Wired remote control (3.5mm stereo) - loop out available for daisy chaining | |
| <ul style="list-style-type: none"> • ±120% Vertical (±648 pixels) • ±30% Horizontal (±288 pixels) | <ul style="list-style-type: none"> • ±100% Vertical (±600 pixels) • ±30% Horizontal (±288 pixels) |
| <ul style="list-style-type: none"> • Lens 0.36 (120") Ultra short throw lens, 630/700/850/1075-GS • Lens 0.75-0.95 Zoom G/GS • Lens 0.95-1.22 Zoom G/GS • Lens Zoom HP G/GS 1.22-1.52 (All G & GS) • Lens 1.52-2.89 Zoom G/GS • Lens 2.9-5.50:1 Zoom G/GS | |
| <ul style="list-style-type: none"> • Normal: 100-240 VAC @ 50/60Hz (w/15A fuse) • Normal mode: 1070W • Normal mode: 10A (100V-240V) | |
| <ul style="list-style-type: none"> • (LxWxH): 19.9 x 22.2 x 7.6" (480 x 555 x 190mm) w/o feet or lens • (LxWxH): 24.1 x 30.4 x 14.9" (599 x 759 x 373mm) • 54.9lbs (24.9kg) w/o lens • 69.9lbs (31.7kg) | |



Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161

Russia
ph: +7 (495) 930 8961

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6030 0500

Colombia
ph: +57 (318) 447 3179

Eastern Europe
ph: +36 (0) 1 47 48 138

France
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)
ph: +49 221 99 512-0

Germany (Mönchengladbach)
ph: +49 2161 566200

India
ph: +91 (080) 6708 9999

Japan
ph: +81 3 3599 7481

Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000

Singapore
ph: +65 6877 8737

South Korea
ph: +82 2 702 1601

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 (0) 4 503 6800

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014



For the most current specification information, please visit www.christiedigital.com

Copyright 2019 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4760 Feb 19

CHRISTIE®